

POWER

RIDE

TECHNICAL SPECIFICATION - POWERRIDE PRO

Rim Size	- 27.5"
Frame	- Aluminum Alloy MTB Frame, 27.5*2.125, 19 inch
Fork	- Shock Absorbing Fork, Steel, 38mm
Rim	- Aluminum Alloy Double Wall Rim, 27.5 inch
Handlebar	- Steel 680mm*φ22.2*2.2T Curved Shape
Stem	- Aluminum Alloy 80mm
Front Brake	- JAK-7 Disc Brake
Rear Brake	- JAK-7 Disc Brake
Colours	- Black and Grey
Front Hub	- High Carbon Steel
BB parts	- Sealed
Chain Wheel	- Aluminum Alloy, Black, Single Piece 36T*170mm
Free Wheel	- Shiamno TZ500-7, 7s Freewheel
Chain	- TEC 114L Chain
Pedal	- Plastic, YH-20X, Black, with Reflector
Saddle	- Black Saddle, PVC+PU+PP, ED Beam, ED Clip
Seat Post	- 30.4*300mm*2.4T Alloy Black
Stander	- High Carbon Steel, ED, Double Hole, Single Side, 260mm
Tire	- Kylin 27.5*2.125
Front Light & Horn	- With Horn and on-off, D-018 36V
Gear Shifter	- Shimano TX50 shift lever
Front Derailleur	- Shimano TZ500
Rear Derailleur	- Shimano TY200
Motor	- 36V 250W Brushless
Controller	- 25KM/H 36V Controller
Battery	- 36V 10.4AH Cell Battery
Sensor	- 720mm
E brake lever	- Electric Brake Lever
Charger	- 36V 2A, Plastic with CE Certificate
Display with throttle	- Display HKP1 Model 3 PAS Level/Thumb Throttle
Tool Bag	- M4 L Shape Spanner, M5 L Shape Spanner, 8-10 Open Spanner, 13-15 Open Spanner